


	<p>1. Sikkerhedsstrop demonteres dvs. Popnitte bores ud m. ø5 bor</p> <p>1. Detach the safety strap by drilling out the pop rivet</p> <p>1. Demontieren Sie die Sicherheitsschlaufe bei abbohren des Popniets</p>
	<p>2. Afkort S-trækstang 70mm.</p> <p>2. Shorten the towbar 70mm</p> <p>2. Kürzen Sie die Deichsel 70mm</p>
	<p>3. Fjern savegrat.</p> <p>3. Remove burr.</p> <p>3. Entfernen Sie Grat.</p>
	<p>4. Isæt Weberkobling og bor ø5hul helt igennem kobling og S-trækstang.</p> <p>4. Mount the Weber coupling and drill a 5mm hole all through the coupling and the towbar</p> <p>4. Setzen Sie die Kupplung und bohren Sie ein 5mm Loch durch Kupplung sowohl als Deichsel.</p>
	<p>5. Monter støttefod/sikkerhedsstrop. Husk at lægge strop dobbelt så skruer går igennem begge huller i stroppen</p> <p>5. Mount the propstand and safety strap. Please put the strap around twice with the bolt entering both holes in the strap.</p> <p>5. Montieren Sie Stützbein und Sicherheitsschlaufe. Bitte die Schlaufe zweimal rund legen, so dass die Schraube zwischen beide Löcher durchgehen.</p>